

VIDEO DOOR PHONE – SPECIFICATION

Part Number	83202S-K	83226S-K	83204TM
Image			
Processor	High-Performance Embedded SOC Processor	High-Performance Embedded SOC Processor	High-Performance Embedded SOC Processor
Operation system	Embedded Linux Operation System	Embedded Linux Operation System	Embedded Linux Operation System
Camera	CMOS Low Illumination 2.0 MP HD Colorful Camera	CMOS Low Illumination 2.0 MP HD Colorful Camera	CMOS Low Illumination 2.0 MP HD Colorful Camera
Video compression standard	H.264	H.264	H.264
Display Screen	4.3-Inch Colorful TFT LCD	4.3-Inch Colorful TFT LCD	10.1-Inch Colorful TFT LCD
Display Resolution	480 × 320	480 × 320	1280 × 800
Operation Method	Physical Keypad	Physical Keypad	Touch Screen
Operation Interface	LCD Display, Easy Menu	LCD Display, Easy Menu	LCD Display, Easy Menu
Standby Current	150mA	150mA	150mA
Working Current	400mA	400mA	400mA
Internal Card Reader	Built-in IC Card Reader	Built-in IC Card Reader	Built-in IC Card Reader
External Card Reader	Wiegand 26, Wiegand 34, or RS-485 IC Reader	Wiegand 26, Wiegand 34, or RS-485 IC Reader	RS-485 IC Reader
Door Magnetic Detection	Detects Door Magnetic Status	Detects Door Magnetic Status	Detects Door Magnetic Status
Light Supplement Mode	Visible Light Supplement	Visible Light Supplement	Visible Light Supplement
Ethernet	10/100/1000 Mbps Self-adaptive Ethernet	10/100/1000 Mbps Self-adaptive Ethernet	10/100/1000 Mbps Self-adaptive Ethernet
Network Protocol	TCP/IP	TCP/IP	TCP/IP
Network Interface	1RJ-45 10/100/1000 Mbps Self - adaptive Ethernet Interface	1RJ-45 10/100/1000 Mbps Self - adaptive Ethernet Interface	1RJ-45 10/100/1000 Mbps Self - adaptive Ethernet Interface
Material	Aluminum Alloy	Stainless steel	Aluminum Alloy
Power Supply	DC15V or PoE powered	DC15V or PoE powered	DC15V or PoE powered
Power Consumption	≤15 W	≤15 W	≤15 W
Working Temperature	-40°C to +60°C	-40°C to +60°C	-40°C to +60°C
Working Humidity	10% to 90%	10% to 90%	10% to 90%
IP Protection Level	IP65	IP65	IP65
Dimensions (L * W x H)	365 × 140 × 50mm	369 × 144 × 43mm	338 × 190 × 31mm
Certification	CE, ROHS, REACH, WEEE, RED, COC	CE, ROHS, REACH, WEEE, RED, COC	CE, ROHS, REACH, WEEE, RED, COC